




BEARING MFG. CORP.

NTN 22328UAVS2 Bearing



Bearing No. 22328UAVS2

22328UAVS2 Bearing 2D drawings and 3D CAD models

Size	140x300x102 mm
Bore Diameter	140,000 mm
Outer Diameter	300,000 mm
Width	102,000 mm
d	140,000 mm
D	300,000 mm
H	102,000 mm
Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	33.73
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch - Metric	Metric
Long Description	140MM Straight Bore; 300MM Outside Diameter; 102MM Width;



BEARING MFG. CORP.

	C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0
Width	4.016 Inch 102 Millimeter
Outside Diameter	11.811 Inch 300 Millimeter
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Bore	5.512 Inch 140 Millimeter
bore diameter:	140 mm
operating temperature range:	-40 to 120 ° C
outside diameter:	300 mm
cage material:	Brass
overall width:	102 mm
bearing material:	Through Hardened Steel
bore type:	Straight
cage type:	Machined
outer ring type:	Not Split
precision rating:	Not Rated
internal clearance:	Upper 2/3 of C4 range
finish/coating:	Uncoated
closure type:	Open
outer ring width:	102 mm
lubrication hole type:	Lubrication Groove & Hole



BEARING MFG.CORP.

inner ring width:	102 mm
dynamic load capacity:	1110000 N
fillet radius:	4 mm
static load capacity:	1110000 N
series:	223
maximum rpm:	1300 rpm
manufacturer product page:	Click here